BATHGATE

FLOORING

Europed & M, E Range Support Pedestal

Tested in accordance with BSEN 12825 for raised access floors

Europed / BS EN Pedestal Options

A pedestal range allowing us to offer total flexibility whilst maintaining the highest possible quality standard and ensuring fast reaction and a reliable service. Steel pedestals are electro plated and coated with an environmentally friendly clear passivation.

Fully compliant and tested with the Permaflor panel to BSEN12825:2001.

- 1. Anti-vibration cap
- 2. 2mm or 3.5mm thick steel head
- 3. Threaded hollow steel tube 22mm or 25.5 OD
- 4. 3mm thick locking nut
- 5. Steel 100mm diameter circular base or 80 x 80mm square by 2.5mm thick
- 6. Pre-formed holes for optional mechanical fixing to slab



PEDESTAL GRADE	HEAD SIZE	TUBE SIZE	BASE SIZE	VOID RANGE
Euro / BS EN M Range	90mm diameter 3.5mm thick	22mm OD	100mm diameter	50 - 250mm*
BS EN M Range	90mm diameter 2mm thick	22mm OD	80 x 80mm	50 - 185mm*
BS EN E Range	90mm diameter 2mm thick	25.5mm OD	80 x 80mm	50 - 475mm*

Head

Mild Steel Disc 90mm in diameter in 2mm or 3.5mm thick steel welded onto a mild steel tube reduced at one end to take the mating thread of the base. The locking nut allows fine adjustment of the head to the correct finished floor height and can then be fixed with adhesive. A variety of different pedestal caps are available to suit perimeter, stringers etc.


Threaded Socket

22mm and 25.5mm Threaded tube.

Base

The base is mild steel, 100mm diameter circular design for the Euro or 80mm x 80mm square plate for the E and M range, with the central boss housing the steel stud. Punched holes are incorporated to facilitate mechanical fixings if required. Earthing cables may also be pre-fitted. Strengthening ribs are pressed in for added stability. Earthing clips may also be supplied.

* Pedestals required outside of this height range are also available.



Bathgate Flooring Unit 6G Thorn Business Park Hereford HR2 6JT

